

503 LED



Características / Characteristics

Luminaria LED para aplicaciones comerciales, industriales y arquitectónicas.

LED fixture for commercial, industrial and architectural applications.

Luminaria para empotrar en cielo suspendido de tipo "T" invertido de 1 pulgada de alto, de madera, cielo Gypsum o tabla yeso.


LED fixture for recessed installation in suspended ceilings, inverted "T" type of 1 inch high, of wood or Gypsum.

Temperatura de color 4000K y 6500K. Para otras temperaturas de color consulte con su asesor comercial.

Color temperature 4000K and 6500K. For other color temperatures consult your business advisor.




Dimensiones generales / General dimensions



Dimensión Nominal	A (mm)	B (mm)	C (mm)
(2x2)	607	602	101
(2x4)	1216	602	101

Curva Fotométrica / Photometric Curve



UL 503 LED 6 10000lm 2x4 Opal

Accesorios / Accessories

Código/Code	Difusor/Diffuser	Código/Code	Difusor/Diffuser
DIFUSOR 503-408		KIT MARCO GYPSUM	
P08550-36	LED 2X2 PRISMATICO	P06423-36	2X2
P08551-36	LED 2X4 PRISMATICO	P06369-36	2X4
P08552-36	LED 2X2 OPALINO		
P08553-36	LED 2X4 OPALINO		

Información técnica / Technical information

ESPECIFICACIONES / SPECIFICATIONS

Modelo Model	Dimensión Nominal Nominal Dimension	Cantidad de Módulos Quantity of Modules	Potencia Power	Flujo Luminoso Luminous Flux	Difusor Diffuser	Instalación Installation	Temp. de color Color temp.	Eficacia Efficacy	Base Base	Código con batería Code with battery
503 Led	2x2	2	35 W	4000 lm	Sin difusor	Cielo Suspendido	4000 k	>110	P03677-21	P04179-21
	2x2	2	35 W	4000 lm	Sin difusor		6500 k	>110	P02870-21	P04485-21
	2x2	3	45 W	5000 lm	Sin difusor		4000 k	>110	P03400-22	P06976-21
	2x2	3	45 W	5000 lm	Sin difusor		6500 k	>110	P07353-21	P07354-21
	2x4	4	55 W	7000 lm	Sin difusor		4000 k	>110	P03709-22	P02570-36
	2x4	4	55 W	7000 lm	Sin difusor		6500 k	>110	P04426-22	P02644-36
	2x4	4	80 W	10000 lm	Sin difusor		4000 k	>110	P03710-22	P04121-36
	2x4	4	80 W	10000 lm	Sin difusor		6500 k	>110	P04836-22	P08358-36

